## **CLAIMS**

What is claimed is:

1. An article of clothing comprising: an outer fabric layer having an outer opening;

5

an inner fabric layer coupled to the outer fabric layer and having an inner opening, the inner fabric layer being substantially waterproof; and

a water-resistant closure coupled to the inner fabric layer adjacent the inner opening.

10

- 2. An article of clothing as claimed in claim 1, wherein said outer fabric layer is not waterproof.
- 3. An article of clothing as claimed in claim 1, wherein said outer fabric layer comprises abrasion-resistant nylon.

15

25

- 4. An article of clothing as claimed in claim 1, wherein said inner fabric layer comprises polymer-coated nylon.
- 5. An article of clothing as claimed in claim 1, wherein said inner opening is substantially aligned with said outer opening.
  - 6. An article of clothing as claimed in claim 1, wherein said waterresistant closure is movable between an open position, which allows air to pass through the inner opening, and a closed position, which substantially prevents water from passing through the inner opening.

10

- 7. An article of clothing as claimed in claim 1, wherein the water-resistant closure comprises a water-resistant zipper.
- 8. An article of clothing as claimed in claim 1, further comprising a venting material secured to the inner fabric layer and covering at least portion of the inner opening, the venting material allowing passage of air therethrough.
  - 9. An article of clothing as claimed in claim 8, wherein the venting material includes a plurality of holes therethrough.

	10.	A method of making an article of clothing comprising:
providing an outer fa		ling an outer fabric layer defining an outer opening;
	provid	ling a substantially waterproof inner fabric layer defining an inner
openin	ıg;	

providing a water-resistant closure;

coupling the water-resistant closure adjacent the inner opening; and

coupling the waterproof inner fabric layer to the outer fabric layer to

extend across the outer opening.

11. The method of claim 10 further comprising:

aligning the inner opening with the outer opening;

providing a venting material; and

securing the venting material to the inner fabric layer to cover at least a

portion of the inner opening.

15

10